



WATERITE TECHNOLOGIES, INC.
3-75 Meridian Drive
Winnipeg, MB
Canada R2R 2V9
PHONE: (204) 786-1604
FAX: (204) 783-1599
waterite@waterite.com
www.waterite.com

**WATERITE TECHNOLOGIES, INC.
PRODUCT SPECIFICATION SHEET
FIL-SPP-002**

**SPUN POLYPROPYLENE SEDIMENT
FILTER CARTRIDGE**

TYPE: 2 ½" and 4 ½" cartridges for 10" and 20" standard and full flow (Big Blue) housings
FEED: Municipal or well water
TEMP. RANGE: 5.0°C to 6.0°C
CAPACITY: determined by raw water turbidity
MICRON RATING: 1, 5 and 20 micron nominal
COLOUR: white
MATERIAL: Virgin melt-blown polypropylene
All materials conform to NSF 42/53
PACKAGING MODELS: Plastic shrink wrapped and labeled
PP10-01, PP10-05, PP10-20 PP20-01, PP20-05, PP10B-05, PP10B-20, PP20B-05, PP20B-20
PERFORMANCE:

Cartridge Model	Micron Rating	Initial ΔP @ Flow Rate
PP10-01	1	0.6 psi @ 5 GPM
PP10-05	5	0.2 psi @ 5 GPM
PP10-20	20	0.2 psi @ 5 GPM
PP20-01	1	0.6 psi @ 10 GPM
PP20-05	5	0.6 psi @ 10 GPM
PP10B-05	5	≤1 psi @ 10 GPM
PP10B-20	20	≤1 psi @ 10 GPM
PP20B-05	5	≤1 psi @ 20 GPM
PP20B-20	20	≤1 psi @ 20 GPM

Exce1pure™